

SB SERIES STRAW BLOWERS



ENGINE OR PTO DRIVES

Power the blower with Tractor PTO or add an optional engine for greater flexibility.

50ft DISCHARGE

50 ft. discharge means greater precision with mulch application of 1-2 bales per minute.

AUTOMATIC BALE FEED

The SB Series automatic bale feed processes the entire bale, eliminating slab feeding.

SB 4000 STRAW BLOWER



FIVE TO SEVEN BALES PER MINUTE OUTPUT

60-80ft. discharge and 5-7 bales per minute allows for a quick mulch application.

360° SPINNING

The SB 4000 model spout offering great any landscaping task

MODEL	SB 1300	SB 1800	SB 5400
Power source	Honda™ GX390	Kohler™ 440	PTO 540
Power discharge	45-50 ft. distance with 6" x 30' hose	45-50 ft. distance with 6" x 30' hose	50-55 ft. distance with 6" x 30' hose
Dimensions	31"W x 51"L x 55"H	31"W x 51"L x 55"H	31"W x 55"L x 60"H
Weight	460 lbs.	500 lbs.	525 lbs.
Bales/minute	1-1.5 bales	1.5-2 bales	1-2 bales
Rotor	16" dia./32 knives	16" dia./32 knives	16" dia./32 knives
Steel impeller	18" dia./0.25" steel	18" dia./0.25" steel	18" dia./0.25" steel

The manufacturer reserves the right to make changes in engineering, design, and specifications or add improvements at any time without notice or obligation.

MODEL	SB 4000
Engine	Yamaha™ 5400
Power discharge	60-80 ft. distance with 6" x 30' hose
Dimensions	31"W x 55"L x 60"H
Weight	1000 lbs.
Bales/minute	5-7 bales
Rotor	16" dia./32 knives
Steel impeller	18" dia./0.25" steel

The manufacturer reserves the right to make changes in engineering, design, and specifications or add improvements at any time without notice or obligation.